Validity expires on 15-02-2023



Menta suri

Proceedings of the State Environment Impact Assessment Authority Kerala

Present: Prof. (Dr.) K.P. Joy, Chairman; Dr. J. Subhashini, Member and Sri. P. Mara Pandiyan, I.A.S, Member Secretary.

Sub: Application for environmental clearance for the proposed expansion of existing IT/ITES SEZ campus project (M/s Infosys Limited) in Sy. No. 198(p), 143(p), 180(p), 181(p), 190(p), 191(p), 192(p), 200(p), 203(p), 183, 184, 186, 188, 194, 195, 196, 197, 199, 201, 202(p), 204(p), 223(p) and 224(p) in Block No. 18 at Attipra Village, Thiruvananthapuram Taluk, Thiruvananthapuram District by Adv. Dr. P. Ramadas Kamath, U.-Environmental Clearance-Granted.

STATE ENVIRONMENTAL IMPACT ASSESSMENT AUTHORITY

No. 647/SEIAA/EC1/4943/2013

dated, Thiruvananthapuram 16-02-2016

- Read:
- Application dated 15.10.2014 submitted by Sri. Ramadas Kamath, U., Sr. Vice President- Head Administration Facilities, Infrastructure & Security, M/s Infosys Limited, Plot No.1, Technopark Campus II, Attipra Village, Thiruvananthapuram-695583
- 2. Minutes of the 40th meeting of SEAC held on 29-05-2015.
- 3. Minutes of the 49th meeting of SEAC held on 07/08-12-2015.
- 4. Minutes of the 48th meeting of SEIAA held on 23-01-2016.

Environmental Clearance No. 13 /2016

Sri. Ramadas Kamath, U., Sr. Vice President- Head Administration Facilities, Infrastructure & Security, M/s Infosys Limited, Plot No.1, Technopark Campus II, Attipra Village, Thiruvananthapuram-695583 applied for Environmental Clearance under the EIA Notification dated 14-09-2006 for the proposed expansion of existing IT/ITES SEZ campus project (M/s Infosys Limited) in Sy. No. 198(p), 143(p), 180(p), 181(p), 190(p), 191(p), 192(p), 200(p), 203(p), 183, 184, 186, 188, 194, 195, 196, 197, 199, 201, 202(p), 204(p), 223(p) and 224(p) in Block No. 18 at Attipra Village, Thiruvananthapuram Taluk, Thiruvananthapuram District. The project comes under the Category B, 8(a) of Schedule of EIA Notification 2006. No forest land is involved in the present project. Project description is as under;

Item	Description provided by the proponent
Name of project	Environmental Clearance for the proposed expansion (Phase-2) of
	existing IT/ITES SEZ campus (Phase-1) project to be developed by
	M/s INFOSYS LIMITED.
	Proposed expansion (Phase-2) of existing IT/ITES SEZ campus
Brief description of the	(Phase-1) project with total plot area 20.243 ha. (2,02,343.60 sq.m.)
project	and total built-up area 3,76,369.96 sq.m. (E.C. obtained built-up area =
	1,36,566 sq.m. + Proposed built-up area = 2,39,803.96 sq. m.)
Category/Subcategory &	Category 'B', Schedule 8 (b)
Schedule	SMENT AUTH

Lo	ocation Sy no/ district,	Sy. No. 198(p), 143(p), 180(p), 181(p), 190(p), 191(p), 192(p), 200(p),			
Taluk/ village etc.		203(p), 183, 184, 186, 188, 194, 195, 196, 197, 199, 201, 202(p),			
Turdin viriage etc.		204(p), 223(p) and 224(p) in Block No. 18 at Attipra Village,			
		Thiruvananthapuram Taluk, Thiruvananthapuram District.			
G	PS co-ordinates	Latitude (N) 8032'20.87" to 8031'50.86"			
		Longitude (E) 76053'12.07" to 76052'56.71"			
	Built up area (in m2)	3,76,369.96 sq.m.			
		(E.C. obtained for built-up area = 1,36,566 sq. m. +			
t s		Proposed built-up area = 2, 39,803.96 sq. m.)			
jec	No. of floors	Ground + 10 floors			
brc	Maximum height from	48.30 m.			
ion	ground level				
for Construction projects	Facilities proposed	IT/ITES Buildings (SDB-1, 2, 3, 4, 5 & 6), MLCP, Food court-1 & 2,			
nst		First Aid / Health Centre, Hostel block, Services / Utilities block &			
Ö		Recreational areas, multi-level car parking block, STP, solid waste			
<u>ā</u>		collection and processing facilities etc.			
	Sufficiency of parking	2,278 Cars + 2,316 Two wheelers + 33 Buses + Promotion of			
	spaces/ traffic management	public transport			
<u> </u>		WATER			
W	ater requirement &	The total domestic water requirement of 1,115 KLD (which includes			
l	urces	daily fresh water requirement of 711.50 KL). Treated water from			
		STP to be used for flushing of toilets 675 KLD, Horticulture			
		requirement will be of 91 KLD and Make-up water requirement for			
		cooling towers attached to HVAC system 64 KLD			
		Source: - Stored Rain water (Tanks & Ponds), Technopark water			
		supply and treated water from STP.			
R'	WH units proposed	The project has provision for rain water storage tanks / ponds			
		which will be used as source of water during rainy days & non-			
		rainy days.			
Fa	cilities for liquid waste	After expansion a total of domestic sewage about 923 KL/day will be			
tre	eatment	generated, which will be treated through STPs. (There is an existing			
		STP having a capacity of 300 KLD and after expansion, additional 2			
	• •	STPs to be developed within the project premises.)			
	poundment, damming,	A thodu (storm water stream) is passing through project site which			
	lverting, realignment or	divides the total plot in two portions. There are bridges made across			
4 .	her changes to the	the stream. No impoundment, damming, realignment or other			
hydrology of watercourses		changes to the hydrology of surface water courses is proposed.			
or aquifers.		W. day 1'd			
Water quality meeting		Water quality meets requirements after the treatment of water			
requirements Provisions for use of		(filtration & disinfection).			
		Treated water from STP to be used for flushing of toilets, horticulture water requirement and make-up water requirement for			
recycled water		cooling towers attached to HVAC system.			
LAND					
Δ.	ccess road to the site –	> 45 m. wide (ROW) (NH-47 bye-pass), S side			
Width & Condition		No need to construct any approach road. (Only internal roads will be			
Idda de Collaition		constructed for traffic movement and parking.			
Storage of explosives		➤ All precautionary measures in the storage & handling of HSD &			
/hazardous substances		PNG waste will be followed.			

(green bins) & non-biodegradable waste (blue bins). > The recyclable waste like packaging material, paper etc. would be sold through vendors. > Bio-degradable waste & sludge from STP would be disposed through the proposed Bio-gas generation plant and Organic waste converter (OWC). > The manure from the Bio-gas generation facility unit will be utilized for green area development within the premises. Proneness to natural hazards. > As per the Indian Standards Sestinic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Top soil, overburden etc. Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR	1 1'4 C	Collection & garagetian within the gite (his degradable waste			
> The recyclable waste like packaging material, paper etc. would be sold through vendors. > Bio-degradable waste & sludge from STP would be disposed through the proposed Bio-gas generation plant and Organic waste converter (OWC). > The manure from the Bio-gas generation facility unit will be utilized for green area development within the premises. Proneness to natural hazards. > As per the Indian Standards Seismic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Top soil, overburden etc. > Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Air quality meeting requirements Dust emission from construction phase	Facility for solid waste	Collection & segregation within the site (bio-degradable waste			
sold through vendors. > Bio-degradable waste & sludge from STP would be disposed through the proposed Bio-gas generation plant and Organic waste converter (OWC). > The manure from the Bio-gas generation facility unit will be utilized for green area development within the premises. Proneness to natural hazards. > As per the Indian Standards Seismic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, crosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Posoil, overburden etc. > Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Air quality meeting requirements Dust emission from construction phase	management.				
Bio-degradable waste & sludge from STP would be disposed through the proposed Bio-gas generation plant and Organic waste converter (OWC). The manure from the Bio-gas generation facility unit will be utilized for green area development within the premises. As per the Indian Standards Seismic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, crosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Top soil, overburden etc. Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR					
the proposed Bio-gas generation plant and Organic waste converter (OWC). The manure from the Bio-gas generation facility unit will be utilized for green area development within the premises. Proneness to natural hazards. As per the Indian Standards Seismic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proposent stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Air quality meeting requirements Dust emission from construction phase Construction phase Construction phase Dust generated during unloading of construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. It is proposed to have D. G. sets of the existing building and 2,000 kVAx3 nos. for the proposed facility. Price will be some noise the proposed facility. The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.					
COWC).					
Proneness to natural hazards. Proneness to natural hazards. Proneness to natural hazards. Proneness to natural hazards. As per the Indian Standards Seismic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Pexcavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Air quality meeting requirements Dust emission from construction phase Poust emission from construction phase Sprinklers for suppression of dust will be installed during unloading and handling of construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Pile foundation excavation works generate vibration Pouring Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration of pile foundation.		* *			
Froneness to natural hazards. As per the Indian Standards Seismic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Top soil, overburden etc. Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Dust emission from construction phase Construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels There are 2,000 kVAx2 nos. D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements There will be some noise generate due to cutting of marble and other stone materials. Puile foundation excavation will be foundation.					
Proneness to natural hazards. As per the Indian Standards Seismic Zoning Map, the proposed area comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Description of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR					
comes under Zone-III, moderate damage risk zone. The proponent stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Top soil, overburden etc. Descavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Air quality meeting requirements Dust emission from construction phase Dust emission from poperations etc. there will be batching plants for the production of concrete mix. Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels Dust generated during unloading of construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Dust emission from proposed project does not envisage any major air pollutant generating source except D.G. sets and vehicular movement during construction and operation phase. There are 2,000 kVAx2 nos. D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There will be some noise generate due to cutting of marble and other stone materials. Puir foundation excavation of proposed facility. Dury rotary drilling machines will be engaged for excavation works generate vibration of pile foundation.	Propenses to natural hazards				
stated that the project area is not prone to earthquake, erosion, subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR	Tronchess to natural nazards.				
subsidence and cloud-burst. There is no hilly area around the project site; there is no chance of landslides. > Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Air quality meeting requirements Dust emission from construction phase Dust generated during unloading of construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. > Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. > Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels During Construction Phase: There are 2,000 kVAx2 nos. D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation works generate vibration of pile foundation.					
site; there is no chance of landslides. Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR					
Top soil, overburden etc. Excavation of earthwork will be carried out at site. The top soil which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR					
which is fertile will be kept at site for landscaping work, back filling & internal road construction purposes. AIR Air quality meeting requirements Dust emission from construction phase Construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements Pouring Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration Works generate vibration output during construction and operation of pile foundation.	Top soil, overburden etc.				
Air quality meeting requirements Dust emission from construction phase Dust generated during unloading of construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements Pouring Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration Only rotary drilling machines will be engaged for excavation of pile foundation.					
Air quality meeting requirements Dust emission from construction phase Dust generated during unloading of construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control.		& internal road construction purposes.			
requirements construction phase construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. > Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. > Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Emissions from combustion of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation works generate vibration of pile foundation.		AIR			
requirements construction phase construction materials, drilling and grinding operations etc. there will be batching plants for the production of concrete mix. Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control.	Air quality meeting	Dust emission from > Dust generated during unloading of			
the production of concrete mix. > Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. > Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation works generate vibration of pile foundation.	requirements	construction phase construction materials, drilling and grinding			
> Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. > Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels > The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. > It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. > There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements Noise level meeting requirements > During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. > Pile foundation excavation works generate vibration > Sprinklers for suppression of dust will be installed during unloading and handling of construction materials. > The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. > The PPV levels from the pile diviver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.		operations etc. there will be batching plants for			
installed during unloading and handling of construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements Puring Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration installed during unloading and handling of construction materials. The operation of proposed project does not envisage any major air pollutant generating source except D.G sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.		_			
construction materials. Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements Noise level meeting requirements There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration occupants The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.					
Wind breakers (i.e., barricades with GI sheets) or using shade nets will be used for dust control. Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements Puring Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration Pile foundation of proposed project does not envisage any major air pollutant generating source except D.G sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Only rotary drilling machines will be engaged for excavation of pile foundation.					
or using shade nets will be used for dust control. Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.					
control. Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration Control. The operation of proposed project does not envisage any major air pollutant generating source except D.G sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.					
Emissions from combustion of fossil fuels The operation of proposed project does not envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation works generate vibration Of pile foundation.		ļ			
combustion of fossil fuels envisage any major air pollutant generating source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration of pile foundation.					
fuels source except D.G sets and vehicular movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration Source except D.G sets and vehicular movement during construction and operation. There D.G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. Gonly rotary drilling machines will be engaged for excavation of pile foundation.					
movement during construction and operation phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration of pile foundation.					
phase. It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration phase: The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.		I			
It is proposed to have D. G. sets of 3 nos. of 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration There will be some noise driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.		1			
62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration 62.5 kVA capacity during construction phase. There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.		1 -			
There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration There are 2,000 kVAx2 nos. D. G. sets for the existing building and 2,000 kVAx3 nos. for the proposed facility. The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.					
Roise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration existing building and 2,000 kVAx3 nos. for the proposed facility. The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.					
Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration Phase: The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.					
Noise level meeting requirements During Construction Phase: There will be some noise generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration The PPV levels from the pile driver would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.	·				
There will be some noise generate due to cutting of marble and other stone materials. ➤ Pile foundation excavation works generate vibration There will be some noise generate would be maintained within 15 mm/sec. at 15 m. from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.	Noise level meeting				
generate due to cutting of marble and other stone materials. Pile foundation excavation works generate vibration generate due to cutting of marble and other stone from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.	-				
marble and other stone materials. Pile foundation excavation works generate vibration from the source of generation. Only rotary drilling machines will be engaged for excavation of pile foundation.	requirements				
materials. Pile foundation excavation works generate vibration Only rotary drilling machines will be engaged for excavation of pile foundation.		8			
➤ Pile foundation excavation will be engaged for excavation works generate vibration of pile foundation.					
works generate vibration of pile foundation.					
heavy and light vehicles at high restricted to day time only.	and the second second	1			
speeds may cause increase in Noise generated from Des sets					
ambient noise levels on the shall be shear generators to		ambient noise levels on the shall be sheat generators to			
project road (No significant restrict the noise within the		project road (No significant restrict the noise within the			

.

			impacts)	perm	issible limit.	
Likely	emissions affecting	>	Diesel Generators will be	_	se of low sulphur diesel,	
environ	_		used only during		nission from the D. G. sets	
			, ,		e within the norms.	
Hazard	ous waste generation	>	Used oils from D. G sets,	> These	e will be stored in HDPE	
l	nagement		discarded fuel filters and oil	drum	s in isolated covered	
			filters, discarded generator	facili	ty and this will sold to the	
			batteries etc.		B approved recyclers (M/s.	
				Perfe	ct Alloys, Chengannur;	
				M/s.	Peejay Enterprises,	
				Tripu	nithura; M/s.	
				Petro	chemical, Kochi; M/s Cee	
		<u> </u>		Jee L	ubricaants, Aluva).	
			ENERGY			
	requirement & source	+	MVA, KSEB & D. G. Sets (2,000			
l .	of usage of alternative	>	Solar water heating system for	the hot	water generation and solar	
	resources		power operated street lights.			
	VERSITY					
	e of any endangered	>	There is no Endangered specie	s and no	one species in red listed	
	or red listed category		category			
l	native species and		There are some native tree speci			
genetic	diversity		herbs, grass, climbers existing at site. For the development of the			
			proposed project, existing trees,	shrubs, h	erbs, grass & climbers will	
7 '1 1	1' 1 , CC	_	be cleared.	1 .	1	
Likely	Likely displacement of fauna		Site selected for the project development does not exist as a habitat			
Anyint	roduction of alien /	>	of any species.			
· ·	e species		➤ Invasive species (shrubs):- Chromolaena odorata (L.) R. M. King & H. Rob.			
nivasivo	c species		Lantana camara L.	King & i	i. Kou.	
			Invasive species (Herbs):-			
			Colocasia esculenta (L.) Schott			
			Salvinia adnata Desv.			
			Invasive species (Climbers):-			
			Pueraria phaseoloides (Roxb.) Benth.			
·			Mikania micrantha Kunth			
		1	SOCIAL ASPECTS			
Proximi	ity to nearest	>	The project site is within the Corporation limits and several			
habitati	· ·		houses located within the 500 m. radius.			
			CSR components suggested			
Sl. No.	Description		Approx. Amount proposed		Remarks	
1	Promotion of Education		Recurring = Rs. 21.51 lakhs			
	and Infrastructure Facility		Non-recurring = Rs. 14.42 lakhs			
2 Health Care		Recurring = Rs. 25.29 lakhs		A detailed study on		
*			Non-recurring = Rs. 11.80 lakhs		social status of the	
3	Health Care		Recurring = Rs. 25.29 lakhs		project site surroundings	
			Non-recurring = Rs. 11.80 lakhs		& need base study on	
4 Community		Recurring = Rs. 14.45 lakhs proposed CSR activities				
development			Non-recurring = Rs. 31.80 lakhs		were carried out. The	
5 Environmental			Recurring = Rs. 10.30 lakhs		summary of the report is	
Sustainability			Non-recurring = Rs. 13.00 lakhs		provided.	

Total	Recurring = Rs. 88.12 lakhs			
	Non-recurring = Rs. 73.02 lakhs			
Envt Mgmt plan/ Eco	The proposed project has provision for			
restoration plan (brief details)	> Treatment of sewage and it's fully recycling			
	> The project has made provision for rain water storage tanks /			
	ponds			
	> Bio-gas generation plant & Organic waste converter (OWC)			
	within the project site for disposal of the bio-degradable solid			
	waste along with sludge from the STP			
	> As part of the eco restoration, large number of saplings of native			
	species would be planted.			
	> D.G. sets with noise control measures and stack for flue gas.			
	Sufficient parking as per KMBR.			
Biomedical waste management	➤ Provision of first aid/health care centre within the campus. The			
	bio-medical waste generated from the healthcare centre within			
	the campus is outsourced through IMAGE.			
	➤ An MoU is entered into between the project proponent & the			
	agency for the same.			
E-waste management	Discarded computer parts, monitor, key boards etc. constitutes e-			
	waste and this waste will be stored in an earmarked area.			
•	E-waste will be generated after 4-5 years latency period			
	Separate earmarked space will be provided for e-waste storage.			
	Stored e-waste will be disposed through M/s Earth Sense			
	Recycles Pvt. Ltd., a KSPCB approved agency for disposal of e-			
	waste as per E Waste (Management & Handling) Rules, 2012.			
Litigation, if any, against the project	No.			
Total cost of the project with details	1265.25 crores			
Details of Authorised Signatory	Ramadas Kamath, U.,			
	Sr. Vice President- Head Administration Facilities,			
	Infrastructure & Security,			
	M/s Infosys Limited, Plot No.1,			
	Technopark Campus II,			
	Attipra Village,			
<u> </u>	Thiruvananthapuram, Kerala-695583			
Details of NABET approved	M/s Environmental Engineers & Consultants Pvt. Ltd.			
EIA consultant organisation	(at Sr. No. 54 as per MoEF & CC list of Accredited Consultant			
	Organization)			
	Head Office :-			
	A1-198, Janak Puri, New Delhi.			
	Branch Office:-			
	C-306, Kanchanjunga Apartments,			
A service serv	Palarivattom P.O., Kochi, Kerala.			

2. The proposal was placed in 40th meeting of SEAC held on 29th May 2015. As the proponent could not attend the meeting, the proposal was considered in the 49th meeting of SEAC held on 7th & 8th December 2015m as Agenda Item no. 49.16. Further to the intimation of SEAC, the proponent along with the consultant attended the meeting and the consultant made a brief power-point presentation. The samittee observed that instead of applying for the ToR for EIA, the proponent on 17.10.2014 subtracted an application for EC without draft ToR. SEIAA overlooked the omission and transmitted the application for appraisal and in

was placed before the committee only on its 40th meeting held on 29th May 2015 and though the proponent was requested to be present he was not represented in the meeting. Hence the committee deferred the proposal. Meanwhile the proponent submitted draft ToR on 9.9.2015 to SEIAA. Since it did not come up before the committee for consideration it became deemed on expiry of prescribed time limit. Hence the proponent presented the EIA report before the committee based on the standard ToR. The Committee observed that the proposed area falls under SEZ. EC for the existing building was obtained from MoEF on 4.06.2008.

- 3. The committee observed that a thodu is dividing the project area and the proponent informed that it will be retained and the connecting drain from the thodu will be conserved. The proponent also informed that they have provided sufficient setback from the 110 high tension line which is passing through the northern side of the proposed area. The Committee suggested providing tree belt with native species near the NH side of the proposed area. The proponent informed that they proposed biogas plant and organic waste convertors for solid waste management.
- 4. The Committee appraised the proposal based on Form-I, Form-IA, EIA report and all other documents submitted along with the application and decided to *recommend* for issuance of Environmental Clearance with following specific conditions, in addition to the general conditions stipulated for building projects subject to the production of following documents/details.
 - 1) The emergency parking facility proposed should be ear marked.
 - 2) Adequate drinking water and sanitary facilities should be provided for construction workers at the site. Provision should be made for mobile toilets. The safe disposal of wastewater and solid wastes generated during the construction phase should be ensured.
 - 3) Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
 - 4) Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the sump sites for such materials must be secured so that they should not leach into the ground water.
 - 5) Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the Kerala State Pollution Control Board.
 - 6) The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
 - 7) Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
 - 8) Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfil requirement.
- 5. Hence the proposal was considered by SEIAA in its 48th meeting held on 23.01.2016 and the Authority considered the recommendations and decided to grant E.C subject to the above and the additional specific condition that "a tree belt shall be formed with native species near the NH side of the proposed area", and the general condition for building projects.

- 6. Environment clearance as per the EIA notification 2006 is hereby accorded for the proposed expansion of existing IT/ITES SEZ campus project (M/s Infosys Limited) in Sy. No. 198(p), 143(p), 180(p), 181(p), 190(p), 191(p), 192(p), 200(p), 203(p), 183, 184, 186, 188, 194, 195, 196, 197, 199, 201, 202(p), 204(p), 223(p) and 224(p) in Block No. 18 at Attipra Village, Thiruvananthapuram Taluk, Thiruvananthapuram District by Adv. Dr. P. Ramadas Kamath, U. for M/s. Infosys Limited, subject to the clarifications and conditions in paras 5 and 6 above. The clearance will be subject to all the environmental impact mitigation and management measures specified in the documents submitted by the project proponent to SEIAA, and the mitigation measures specified against each in the table in para 1 above. The assurance in form 1A of the application (Appendix II) and clarifications given by the proponent will be deemed to be part of these proceedings as if incorporated herein. Also the general conditions for projects other than mining appended hereto the following green guidelines will be applicable and have to be strictly adhered to.
 - Technology and capacity of the STP to be indicated with discharge point (if any) of the treated effluent.
 - Effluent water not conforming to specifications shall not be let out to water bodies
 - Maximum reuse of grey water for toilet flushing and gardening and construction work shall be ensured.
 - Dual plumbing for flushing shall be done.
 - Provisions for disposal of e-wastes, solid wastes, non-biodegradables and separate parking facility for the buildings shall be provided.
 - Generation of solar energy to be mandatory for own use and/or to be provided to the grid.
 - Mitigation measures to reduce carbon dioxide production as part of climate change action shall be adopted.
- 7. Validity of the Environmental Clearance will be seven years from 01-10-2015, subject to earlier review in the event of noncompliance or violation of any of the conditions stipulated herein.
- 8. Compliance of the conditions herein will be monitored by the Directorate of Environment and Climate Change or its agencies and also by the Regional Office of the Ministry of Environment and Forests, Govt. of India, Bangalore.
 - Necessary assistance for entry and inspection by the concerned officials and staff should be provided by the project proponents.
 - Instances of violation if any shall be reported to the District Collector, Malappuram to take legal ii) action under the Environment (Protection) Act 1986.
- 9. The given address for correspondence with the authorized signatory of the project, Sri. Ramadas Kamath, U., Sr. Vice President- Head Administration Facilities, Infrastructure & Security, M/s Infosys Limited, Plot No.1, Technopark Campus II, Attipra Village, Thiruvananthapuram-695583.

Sd/

P. Mara Pandiyan., I.A.S Member Secretary (SEIA

& Additional Chief Secretary the Contemporary Additional Chief Secretary the Contemporary t Environment & Fores Department

Government of Kerala.

To,

Sri. Ramadas Kamath, U., Sr. Vice President- Head Administration Facilities, Infrastructure & Security, M/s Infosys Limited, Plot No.1, Technopark Campus II, Attipra Village, Thiruvananthapuram-695583

Copy to:

- 1. MoEF Regional Office, Southern Zone, Kendriya Sadan, 4th Floor, E&F Wing, II Block, Koramangala, Bangalore-560034
- 2. The Principal Secretary to Government, Environment Department, Government of Kerala
- 3. The District Collector, Thiruvananthapuram.
- 4. Principal Secretary, IT & Electronic Department.
- 5. The Secretary, Zonal Office of Muncipal Corporation of Thiruvananthapuram, Kachani-Aruvikkara Road, Vattiyoorkavu, Nettayam, Thiruvananthapuram-695013
- 6. Chairman, SEIAA, Kerala.
- 7. Website
- 8. Stock file

9. O/c

Forwarded/ By order

Administrator SEIAA

GENERAL CONDITIONS (for projects other than mining)

- (i) Rain Water Harvesting capacity should be installed as per the prevailing provisions of KMBR / KPBR, unless otherwise specified elsewhere.
- (ii) Environment Monitoring Cell as agreed under the affidavit filed by the proponent should be formed and made functional.
- (iii) Suitable avenue trees should be planted along either side of the tarred road and open parking areas, if any, inclusive of approach road and internal roads.
- (iv) The project shall incorporate devices for solar energy generation and utilization to the maximum possible extent with the possibility of contributing the same to the national grid in future.
- (v) Safety measures should be implemented as per the Fire and Safety Regulations.
- (vi) STP should be installed and made functional as per KSPCB guidelines including that for solid waste management.
- (vii) The conditions specified in the Companies Act, 2013 should be observed for Corporate Social Responsibility.
- (viii) The proponent should plant trees at least 5 times of the loss that has been occurred while clearing the land for the project.
 - (ix) Consent from Kerala State Pollution Control Board under Water and Air Act(s) should be obtained before initiating activity.
 - (x) All other statutory clearances should be obtained, as applicable, by project proponents from the respective competent authorities including that for blasting and storage of explosives.
 - (xi) In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Authority.
- (xii) The Authority reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environment (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- (xiii) The stipulations by Statutory Authorities under different Acts and Notifications should be complied with, including the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.
- (xiv) The project proponent should advertise in at least two local newspapers widely circulated in the region, one of which (both the advertisement and the newspaper) shall be in the vernacular language informing that the project has been accorded Environmental Clearance and copies of clearance letters are available with the Department of Environment and Climate Change, Govt. of Kerala and may also be seen on the website of the Authority at www.seiaakerala.org. The advertisement should be made within 10 days from the date of receipt of the Clearance letter and a copy of the same signed in all pages should be forwarded to the office of this Authority as confirmation.
- (xv) A copy of the clearance letter shall be sent by the proponent to concerned Grama Panchayat/ District Panchayat/ Municipality/Corporation/Urban Local Body and also to the Local NGO, if any, from whom suggestions / representations, if any, were received while processing the proposal. The Environmental Clearance shall also be put on the website of the company by the proponent.
- (xvi) The proponent shall submit half yearly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) and upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the respective Regional Office of MoEF, Govt. of India and also to the Directorate of Environment and Climate Change, Govt. of Kerala.
- (xvii) The details of Environmental Clearance should be prominently displayed in a metallic board of 3 ft x 3 ft with green background and yellow letters of Times New Roman font of size of not less than 40.
- (xviii) The proponent should provide notarized affidavit (indicating the number and date of Environmental Clearance proceedings) that all the conditions stipulated in the EC shall be scrupulously followed.

